

PRODUCTS CATALOG

Non Upset End Couplings – NUE							
Coupling Sizes	Outside Diameter		Mass	Box Qty	Weight / Box	Container Qty	
Inch	Inch		Kg	Nos	Kg	Nos	
1.05	1.313		0.23	8200	1936	82000	
1.315	1.66		0.38	5000	1950	50000	
1.66	2.054		0.59	3200	1938	32000	
1.9	2.2		0.56	3400	1954	34000	
2 3/8	2.875		1.28	1450	1906	14500	
2 7/8	3.5		2.34	800	1922	8000	
3 1/2	4.25		3.71	500	1905	5000	
4	4.75		4.35	440	1964	4400	
4 1/2	5.2		4.89	365	1835	3650	
External Upset End Couplings -EUE							
Coupling	Outside Diameter		Mass Regular & Special Bevel	Mass of	Qty /Box	Weight / Box	Container
	Regular &Special	Special					Qty
Size	Bevel	Clearance		Special Clearance			
Inch	Inch	Inch	Kg	Kg	Nos	Kg	Nos
1.05	1.66		0.38	NA	5000	1945	50000
1.315	1.9		0.57	NA	3300	1926	33000
1.66	2.2		0.68	NA	2800	1949	28000
1.9	2.5		0.84	NA	2250	1935	22500
2 3/8	3.063	2.91	1.55	1.07	1144	1819	11440

PRODUCTS CATALOG

2 7/8	3.668	3.46	2.4	1.55	792	1945	7920
3 1/2	4.5	4.18	4.1	2.38	448	1886	4480
4 1/2	5.563		6.05	NA	294	1823	2940

Casing Long Couplings – 8 RD

Coupling size	Coupling Diameter	Mass		Qty /Box	Weight /Box	Container Qty
		Long Coupling				
inch	Inch	Kg		Nos	Kg	Nos
4 1/2	5	5.96		280	1713	2800
5	5.563	7.86		200	1617	2000
5 1/2	6.3	8.92		210	1918	2100
6 5/8	7.39	11.34		175	2029	1750
7	7.875	13.92		150	2133	1500
7 5/8	8.5	15.63		125	1998	1250
8 5/8	9.625	21.67		80	1778	800
9 5/8	10.625	25.45		80	2081	800

Casing Short Couplings – 8 RD

Coupling Size	Outside Diameter	Short Coupling	Qty / Box	Weight / Box	Container Qty
Inch	Inch	Kg	Nos	Kg	Nos
4 1/2	5.25	5.24	294	1586	2940
5	5.8	6.43	392	2565	3920
5 1/2	6.3	7.34	252	1895	2520
6 5/8	7.39	9.12	200	1869	2000
7	7.875	10.88	150	1677	1500
7 5/8	8.5	12.16	125	1565	1250
8 5/8	9.625	15.62	96	1544	960
9 5/8	10.625	17.85	96	1758	960
10 3/4	11.75	20.58	54	1156	540
11 3/4	12.75	22.43	54	1256	540

PRODUCTS CATALOG

13 3/8	14.375	25.42	54	1418	540		
Casing Buttress Couplings -5 TPI							
	Outside Diameter		Mass				
Coupling	Regular	Special	Regular	Special	Qty / Box	Weight / Box	Container Qty
Size	Size	Clearance		Clearance			
		Size					
inch	inch	inch	KG	KG	NOS	KG	Nos
4 1/2	5.25	4.875	6.89	3.48	280	1974	2800
5	5.8	5.375	8.38	4	200	1721	2000
5 1/2	6.3	5.875	9.30	4.47	210	1998	2100
6 5/8	7.39	7	11.01	5.65	125	1421	1250
7	7.875	7.375	13.98	6.28	150	2175	1500
7 5/8	8.5	8.125	15.82	9.29	125	2142	1250
8 5/8	9.625	9.125	20.86	10.8	80	1713	800
9 5/8	10.625	10.125	23.16	12.02	80	1897	800
10 3/4	11.75	11.25	25.74	13.39	54	1435	540
11 3/4	12.75		28.03		54	1558	540
13 3/8	14.37		31.77		54	1761	540
API Grades, Colour code for Coupling							
Grade	Type		API Colours		Band (X)		
J55 (Tubing)			Bright Green		None		
J55 (Casing)			Bright Green		One White band		
K55			Bright Green		None		
N80	1		Red		None		
N80	Q		Red		One Green band		
L80	1		Red		One Brown band		
P110			White		None		